

Baldor Premier Generators

Baldor Premier Series, the name says it all. Premier's performance and durability have made it the "generator of choice" in the rental and construction industry. Baldor manufactures the Premier Series to the most stringent specifications to ensure that you'll get the highest quality brushless two pole generator on the market. Add to this the quality of an ISO 9001 certified manufacturing plant and a 3 year product warranty and you'll see why the Premier Series has truly earned its name.



R30



OHV30



R60



OHV110E

Premier Features

Switchless Full Pow'R

All the POWER, All the TIME!®

- Premier generators with "Switchless Full Pow'R" do not need a "power switch." We're always full power!
- Plug in 120v or 240v in any combination.
- No need to change voltage settings.
- No need to worry about which cord is plugged in.
- No complicated formulas and instructions.
- Reduces the chance for generator damage.

Automatic Idler

- Automatically idles engine when load is removed.
- Reduces fuel consumption.
- Reduces engine noise.
- Extends engine life.

3-Year Warranty

Focal Vibration System

Optional Dolly Kits

Models: R30, OHV30, R45, R45E, R60, R60E, OHV50H, OHV60, OHV60E, OHV85E, OHV100E, OHV110E

BALDOR
GENERATORS

REAL RELIABLE POWER W

R30 - 3000 Watts

- Robin/Subaru industrial grade engine
- GFCI receptacles
- Low oil shutdown
- Automatic Idler
- Fully enclosed tube frame
- 3-year commercial warranty



OHV30 - 3000 Watts

- Honda commercial grade OHV engine
- AC circuit breakers
- Large fuel tank
- GFCI receptacles
- 3-year commercial warranty



R45/R45E - 4500 Watts

R60/R60E - 6000 Watts

- Robin/Subaru industrial grade engine
- Switchless Full Pow'R
- Automatic Idler
- AC Voltmeter
- Focal Vibration System
- 3-year commercial warranty
- Recoil or Electric Start



OHV50H - 5000 Watts

OHV60/OHV60E - 6000 Watts

- Honda commercial grade OHV engine
- Switchless Full Pow'R
- GFCI receptacles
- Focal Vibration System
- AC Voltmeter
- Automatic Idler
- 3-year commercial warranty
- Recoil or Electric Start



WITH BALDOR GENERATORS

OHV85E - 9000 Watts OHV100E - 10,500 Watts

- Vanguard industrial grade engine
- *Switchless Full Pow'R*
- Electric start with recoil
- *Automatic Idler*
- 3-year commercial warranty



OHV110E - 11,000 Watts

- Honda commercial grade OHV engine
- *Switchless Full Pow'R*
- Electric start
- *Automatic Idler*
- 3-year commercial warranty



Focal Vibration System

- Virtually eliminates harmful vibration
- Less vibration = longer generator life
- Neoprene isolators = more durable than rubber.



Optional Dolly Kits

Two Wheel Kit – Includes 10" pneumatic wheels, fold down handles, power cable storage hanger, axle and mounting hardware.

Four Wheel Kit – 10" pneumatic wheels, axles and mounting hardware.



GFCI receptacles, voltmeter, AC circuit breakers, hourmeter.

OHV110E Panel is displayed to show a variety of features. Panels may vary by model.

Premier Model	R30	R45 or R45E	R60 or R60E	OHV30	OHV50H	OHV60 or OHV60E	OHV110E	OHV85E	OHV100E
Switchless Full Pow'R		•	•		•	•	•	•	•
AC Voltmeter		•	•		•	•	•	•	•
Hourmeter	•	•	•	•	•	•	•	•	•
AC Circuit Breakers	•	•	•	•	•	•	•	•	•
Low Oil Shutdown	•	•	•	•	•	•	•	•	•
Automatic Idler	•	•	•		•	•	•	•	•
Voltage Regulation							•		•
Spark Arrestor Muffler	•	•	•	•	•	•	•	•	•
Extended Run Fuel Tanks	•	•	•	•	•	•	•	•	•
Tubular Roll Cage	•	•	•	•	•	•	•	•	•
Neoprene Isolators	•	•	•	•	•	•	•	•	•
Focal Vibration System (FVS)		•	•		•	•	•	•	•
*3 Year Commercial Warranty	•	•	•	•	•	•	•	•	•

GENERAL FEATURES

Engine Model	Robin/Subaru EH17	Robin/Subaru EH25	Robin/Subaru EH34	Honda GX160	Honda X270	Honda GX340	Honda GX620	Vanguard 303477	Vanguard 350477
Horsepower	5.5 Hp	8.0 Hp	11.0 Hp	5.5 Hp	9.0 Hp	11.0 Hp	20.0Hp	16.0 Hp	18.0 Hp
Cylinder(s)	1	1	1	1	1	1	2	2	2
Displacement – cc	172	231	338	163	270	337	614	480	570
Lubrication System	Splash	Splash	Splash	Splash	Splash	Splash	Pressure	Pressure	Pressure
Starting Systems (Battery not included on Electric Start models)	Recoil	Recoil or 12 Volt with Recoil	Recoil or 12 Volt with Recoil	Recoil	Recoil	Recoil or 12 Volt with Recoil	12 Volt Electric	12 Volt with Recoil	12 Volt with Recoil
Rating	3000W Max.	4500W Max.	6000W Max.	3000W Max.	5000W Max.	6000W Max.	11,000W Max.	9000W Max.	10,500W Max.
	2500W Rated	4000W Rated	5000W Rated	2500W Rated	4000W Rated	5000W Rated	10,000W Rated	8000W Rated	9,500W Rated
	120V AC	120/240V AC	120/240V AC	120V AC	120/240V AC	120/240V AC	120/240V AC	120/240V AC	120/240V AC
	20.8A	33.3/16.7A	41.6/20.8A	20.8A	33.3/16.7A	41.6/20.8A	83.3/41.6A	66.7/33.4A	79.2/39.6A
Sound Ratings									
db(A) at 23 feet (7 meters)	66.9	70.9	72.8	69.9	73.0	72.4	78.0	75.4	75.3
Receptacles									
Straight (5-20R GFCI) 120 V	4-20 Amp	4-20 Amp	4-20 Amp	4-20 Amp	4-20 Amp	4-20 Amp	4-20 Amp	4-20 Amp	4-20 Amp
Twist Lock (L530R) 120 V		1-30 Amp	1-30 Amp		1-30 Amp	1-30 Amp	1-30 Amp	1-30 Amp	1-30 Amp
Twist Lock (L1430R) 120/240 V		1-30 Amp	1-30 Amp		1-30 Amp	1-30 Amp	1-30 Amp	1-30 Amp	1-30 Amp
Twist Lock (CS6369) 120/240 V							1-50 Amp		1-50 Amp
Fuel Capacity (U.S. gallons)	3.2	4.4	4.4	2.8	4.6	4.6	5.8	5.8	5.8
Operational Run Time /1 tankful	6-9 hours	5-9 hours	4.5-8 hours	5-8 hours	6-10 hours	4-7 hours	4-6 hours	4-7 hours	4-6 hours
Dimensions									
Length	22 1/2"	27"	27"	25 1/2"	28"	28"	30"	28"	30"
Width	15 3/4"	18 1/4"	18 1/4"	17 1/2"	20 1/2"	20 1/2"	23"	21 1/2"	23"
Height	20 1/2"	23 1/4"	23 1/4"	18"	22 1/4"	22 1/4"	28 1/2"	27 1/2"	28 1/2"
		(20 1/4"W- R45E)	(20 1/4"W- R60E)						
Weight									
Net Dry	110 lbs.	170 lbs./ 175 lbs.	195 lbs./ 200 lbs.	112 lbs.	170 lbs.	192 lbs./ 206 lbs.	270 lbs.	224 lbs.	270 lbs.

WARNING: Do not connect generator to any building's electrical system unless a disconnect switch has been installed.

NOTES: • Due to our continuing effort for product improvement, specifications subject to change without notice.
* Engine warranty per manufacturer.



3815 Oregon Street • Oshkosh, WI 54902
1-800-872-7697 • (920) 236-4200 • Fax (920) 236-4219



World Headquarters

Baldor Electric Company • P.O. Box 2400 • Fort Smith, AR 72902-2400 U.S.A.
 Phone (479) 646-4711 • Fax (479) 648-5792 • International Fax (479) 648-5895

www.baldor.com